

# 无纸化会议系统接口

v1.0.4

2019.04.26

ReleaseNote

```
v1.04  
修改接口  
oa_login 单点登录  
get_all_files 获取批注文件返回file_id  
get_topics_list 返回议题状态  
delete_user_list 删除人员列表, 如果user_list参数为空, 则删除所有参会人员
```

返回值json字符串, code: 0,成功, 1, 失败。msg:提示信息, list:列表, 如果有。

参数提交, json格式字符串, POST方式提交

## 从oa登录

[http://192.168.1.103/admin/privilege.php?act=oa\\_login](http://192.168.1.103/admin/privilege.php?act=oa_login)

说明: 获取返回的token,跳转到url:<http://192.168.1.103/admin/index.php?token=q55cf6rv97m3cd7rghsnpp06h1>

参数:

```
{  
  "user_name": "manager"  
  "password": "123456"  
}
```

返回值:

```
{  
  "code": 0,  
  "msg": "",  
  "token": "q55cf6rv97m3cd7rghsnpp06h1"  
}
```

## 设置签到二维码

[http://192.168.1.103/oa\\_interface.php?act=set\\_meeting\\_qrcode](http://192.168.1.103/oa_interface.php?act=set_meeting_qrcode)

参数:

```
{  
  "meeting_id": "123456"  
  "qrcode_url": "http://192.168.1.102/qrcode.png"  
}
```

返回值:

```
{  
  "code": 0,  
  "msg": ""  
}
```

## 二维码签到成功

[http://192.168.1.103/oa\\_interface.php?act=qrcode\\_sign\\_success](http://192.168.1.103/oa_interface.php?act=qrcode_sign_success)

说明：二维码签到成功后调用该接口通知无纸化会议系统

参数：

```
{
  "meeting_id": "123456"
  "user_id": "100"
}
```

返回值：

```
{
  "code": 0,
  "msg": ""
}
```

## 获取会议室列表

---

[http://127.0.0.1/oa\\_interface.php?act=get\\_room\\_list](http://127.0.0.1/oa_interface.php?act=get_room_list)

参数：无

返回值：

```
{
  "code": 0,
  "msg": "",
  "list": [
    {
      "room_id": "1",
      "room_name": "房间一",
      "coder_address": "192.168.1.20",
      "broadcast_port1": "39150",
      "broadcast_port2": "39154",
      "broadcast_port3": "0",
      "broadcast_port4": "0"
    },
    {
      "room_id": "8",
      "room_name": "房间二",
      "coder_address": "192.168.1.21",
      "broadcast_port1": "49155",
      "broadcast_port2": "0",
      "broadcast_port3": "0",
      "broadcast_port4": "0"
    },
    {
      "room_id": "9",
      "room_name": "房间3",
      "coder_address": "192.168.1.104",
      "broadcast_port1": "49156",
      "broadcast_port2": "0",
      "broadcast_port3": "0",
      "broadcast_port4": "0"
    }
  ]
}
```

## 获取会议列表

---

[http://127.0.0.1/oa\\_interface.php?act=get\\_meeting\\_list](http://127.0.0.1/oa_interface.php?act=get_meeting_list)

参数：room\_id

```
{
  "room_id": "1";
}
```

返回值:

```
{
  "code": 0,
  "msg": "",
  "list": [
    {
      "meeting_id": "",
      "chairman": "张三丰",
      "meeting_title": "全国人民代表大会第一次全体会议",
      "start_time": "2018-07-28 00:00:00",
      "end_time": "2018-07-29 00:00:00",
      "current": "1"
    }
  ]
}
```

## 新建会议室

---

http://127.0.0.1/oa\_interface.php?act=new\_meeting\_room

参数: room\_id可以为空, 不为空时, 如果room\_id存在, 则返回创建失败

```
{
  "room_id": "10",
  "room_name": "测试新建会议室"
}
```

返回值:

```
{
  "code": 0,
  "msg": "new_meeting_room success."
}
```

## 修改会议室

---

http://127.0.0.1/oa\_interface.php?act=modify\_meeting\_room

参数:

```
{
  "room_id": "10",
  "room_name": "测试修改新建会议室"
}
```

返回值:

```
{
  "code": 0,
  "msg": "modify_meeting_room success."
}
```

## 删除会议室

---

http://127.0.0.1/oa\_interface.php?act=delete\_meeting\_room

参数:

```
{
  "room_id": "10"
}
```

返回值:

```
{
  "code": 0,
  "msg": "delete_meeting_room success."
}
```

## 新建会议

---

[http://127.0.0.1/oa\\_interface.php?act=new\\_meeting](http://127.0.0.1/oa_interface.php?act=new_meeting)

说明: 在指定的会议室创建会议,user\_name为创建会议的人员,可为空。

参数:

```
{
  "user_name": "",
  "room_id": "1",
  "meeting_id": "123456",
  "meeting_name": "测试OA 创建会议",
  "start_time": "1543893237",      (int 类型, unix时间戳)
  "end_time": "1543896237",      (int 类型, unix时间戳)
  "chairman": "张三风"
}
```

返回值:

```
{
  "code": 0,
  "msg": ""
}
```

## 修改会议

---

[http://127.0.0.1/oa\\_interface.php?act=modify\\_meeting](http://127.0.0.1/oa_interface.php?act=modify_meeting)

参数:

```
{
  "meeting_id": "123456",
  "meeting_name": "测试OA 修改会议",
  "start_time": "1543893237",      (int 类型, unix时间戳)
  "end_time": "1543896337",      (int 类型, unix时间戳)
  "chairman": "张三风"
}
```

返回值:

```
{
  "code": 0,
  "msg": ""
}
```

## 取消会议

---

[http://127.0.0.1/oa\\_interface.php?act=cancel\\_meeting](http://127.0.0.1/oa_interface.php?act=cancel_meeting)

参数: {"meeting\_id":"123456"}

返回值:

```
{
  "code": 0,
  "msg": ""
}
```

## 会后获取会议文件

---

http://127.0.0.1/oa\_interface.php?act=get\_all\_files

参数:

```
{
  "meeting_id":"123456"
}
```

返回值: comment\_list为修改过的文件列表

```
{
  "code": 0,
  "msg": "",
  "comment_list": [
    {
      "file_id": "110",
      "file_url": "http://127.0.0.1/meetingfiles/41/pizhu/张三风11-57-28H264数据发送.docx",
      "upload_time": "2018-12-04 11:57:28",
      "user_name": "张三风",
      "meeting_title": "测试OA 修改会议"
    }
  ],
  "file_list": [
    {
      "file_id": "169",
      "file_name": "H264数据发送.docx",
      "file_url": "http://127.0.0.1/meetingfiles/41/61/H264数据发送.docx",
      "upload_time": "2018-12-04 11:35:28",
      "topic_name": "测试议题1",
      "topic_id": "61"
    },
    {
      "file_id": "170",
      "file_name": "保密软件.docx",
      "file_url": "http://127.0.0.1/meetingfiles/41/62/保密软件.docx",
      "upload_time": "2018-12-04 11:35:41",
      "topic_name": "测试议题2",
      "topic_id": "62"
    }
  ]
}
```

## 获取议题列表

---

http://127.0.0.1/oa\_interface.php?act=get\_topics\_list

参数:

```
{
  "meeting_id":"34"
}
```

返回值:

```
{
  "code": 0,
  "msg": "",
  "list": [
    {
      "topic_id": "54",
      "topic_name": "新建议题1",
      "status": "未开始",
      "sortorder": "0",
      "parent_id": "0"
    },
    {
      "topic_id": "55",
      "topic_name": "议题一",
      "status": "已完成",
      "sortorder": "0",
      "parent_id": "0"
    },
    {
      "topic_id": "59",
      "topic_name": "子议题",
      "status": "进行中",
      "sortorder": "0",
      "parent_id": "55"
    }
  ]
}
```

## 新建议题

[http://127.0.0.1/oa\\_interface.php?act=new\\_topic](http://127.0.0.1/oa_interface.php?act=new_topic)

参数: parent\_id:表示父议题的ID, sortorder:议题排序

```
{
  "meeting_id": "34",
  "topic_name": "测试OA新建议题",
  "parent_id": "0",
  "sortorder": "0"
}
```

返回值: topic\_id: 新建议题的ID

```
{
  "code": 0,
  "msg": "",
  "topic_id": 67
}
```

## 修改议题

[http://127.0.0.1/oa\\_interface.php?act=modify\\_topic](http://127.0.0.1/oa_interface.php?act=modify_topic)

参数: topic\_name,parent\_id,sortorder这三项的值可以单独修改或者一起修改

```
{
  "topic_id": "67",
  "topic_name": "测试OA修改议题",
  "parent_id": "0",
  "sortorder": "0"
}
```

```
}  
}
```

返回值:

```
{  
  "code": 0,  
  "msg": "",  
}
```

## 删除议题

http://127.0.0.1/oa\_interface.php?act=delete\_topic

参数:

```
{  
  "topic_id": "67"  
}
```

返回值:

```
{  
  "code": 0,  
  "msg": "",  
}
```

## 添加议题文件

http://127.0.0.1/oa\_interface.php?act=new\_topic\_file\_url

参数: file\_url: 文件下载路径, file\_name: 文件名, topic\_id: 议题id, meeting\_id: 会议ID

```
{  
  "topic_id": "67",  
  "file_name": "测试文件",  
  "file_url": "http://192.168.1.103/测试文件.doc",  
  "meeting_id": "34"  
}
```

返回值:

```
{  
  "code": 0,  
  "msg": "",  
}
```

## 删除议题文件

http://127.0.0.1/oa\_interface.php?act=delete\_topic\_file

参数: file\_id: 文件id

```
{  
  "file_id": "67"  
}
```

返回值:

```
{  
  "code": 0,  
  "msg": "",  
}
```

```
}
```

## 获取设备列表

http://127.0.0.1/oa\_interface.php?act=get\_device\_list

说明：获取会议室中所有的终端列表

参数：room\_id: 会议室ID

```
{  
  "room_id": "1"  
}
```

返回值：device\_name:终端ID

```
{  
  "code": 0,  
  "msg": "",  
  "list": [  
    {  
      "device_name": "231",  
      "ip": "192.168.1.123"  
    },  
    {  
      "device_name": "1",  
      "ip": "192.168.1.26"  
    },  
    {  
      "device_name": "16",  
      "ip": "192.168.1.4"  
    },  
    {  
      "device_name": "4",  
      "ip": "192.168.1.15"  
    },  
    {  
      "device_name": "21",  
      "ip": "192.168.1.39"  
    }  
  ]  
}
```

## 获取文件列表

http://127.0.0.1/oa\_interface.php?act=get\_file\_list

说明：获取会议中所有文件

参数：

```
{  
  "meeting_id": 34  
}
```

返回值：

```
{  
  "code": 0,  
  "msg": "",  
  "file_list": [  
    {  
      "file_id": "163",  
      "file_name": "battery_bg",  
    }  
  ]  
}
```



```
    "file_url": "http://127.0.0.1/meetingfiles/34/54/battery_bg.png",
    "upload_time": "2018-08-09 09:09:13",
    "topic_name": "新建议题1",
    "topic_id": "54"
  },
  {
    "file_id": "165",
    "file_name": "3台MAC地址.xls",
    "file_url": "http://127.0.0.1/meetingfiles/34/54/3台MAC地址.xls",
    "upload_time": "2018-08-23 18:39:08",
    "topic_name": "新建议题1",
    "topic_id": "54"
  },
  {
    "file_id": "168",
    "file_name": "20171212测试问题汇总.docx",
    "file_url": "http://127.0.0.1/meetingfiles/34/54/20171212测试问题汇总.docx",
    "upload_time": "2018-08-23 18:49:59",
    "topic_name": "新建议题1",
    "topic_id": "54"
  },
  {
    "file_id": "171",
    "file_name": "TIM截图20181120162514.png",
    "file_url": "http://127.0.0.1/meetingfiles/34/60/TIM截图20181120162514.png",
    "upload_time": "2018-12-07 17:21:52",
    "topic_name": "44",
    "topic_id": "60"
  }
}
```

```
}
```

## 获取参会人员列表

http://127.0.0.1/oa\_interface.php?act=get\_user\_list

参数:

```
{
  "meeting_id":34
}
```

返回值:

```
{
  "code": 0,
  "msg": "",
  "list": [
    {
      "id": "483",
      "user_name": "张三风",
      "company": "",
      "job": "",
      "device_name": "1"
    }
  ]
}
```

## 新增参会人员列表

http://127.0.0.1/oa\_interface.php?act=new\_user

参数: device\_name:终端ID

```
{
  "meeting_id": 34,
  "user_list": [
    {
      "user_name": "张三风",
      "company": "",
      "job": "",
      "device_name": "1"
    },
    {
      "user_name": "李四",
      "company": "",
      "job": "",
      "device_name": "2"
    }
  ]
}
```

返回值:

```
{
  "code": 0,
  "msg": ""
}
```

## 修改参会人员

[http://127.0.0.1/oa\\_interface.php?act=modify\\_user](http://127.0.0.1/oa_interface.php?act=modify_user)

参数: device\_name:终端ID, 为0时取消名字与终端的关联。

```
{
  "meeting_id": "34",
  "user_name": "",
  "company": "",
  "job": "",
  "device_name": ""
}
```

返回值:

```
{
  "code": 0,
  "msg": ""
}
```

## 删除参会人员列表

[http://127.0.0.1/oa\\_interface.php?act=delete\\_user\\_list](http://127.0.0.1/oa_interface.php?act=delete_user_list)

参数:

```
{
  "meeting_id": 34,
  "user_list": [
    {
      "user_id": "483"
    },
    {
      "user_id": "484"
    }
  ]
}
```

```
}  
}
```

返回值:

```
{  
  "code": 0,  
  "msg": "",  
}
```